

Equipment Inventory - Solid Jacks – Single Action

Item #	Capacity	Stroke	Area	Pressure	Height	O.D.	Rod Dia.	Oil Ca	Weight
J50S	5	0.56	0.994	10,061	1.625	1.7 X 2.6	0.625	0.62	2.2
J53S	5	3.25	0.994	10,061	6.5	1.5	1	3.2	3.26
J100S	10	0.44	2.24	8,948	1.75	2.2 X 3.25	1.77	1	3.3
J101S	10	1	2.24	8,948	3.63	2.25	1.5	2	4
J102S	10	2.125	2.24	8,948	4.75	2.25	1.5	4.8	5
J104S	10	4.125	2.24	8,948	6.25	2.25	1.5	9.5	6.7
J106S	10	6.125	2.24	8,948	9.75	2.25	1.5	13.72	11
J1014S	10	10.125	2.24	8,948	13.75	2.25	1.5	22.6	13
J1014S	10	14.125	2.24	8,948	17.75	2.25	1.5	31.6	16
J151S	15	1.625	3.14	9,549	4.875	2.75	1.75	5.1	7.5
J1512S	15	12	3.14	9,549	16.69	2.75	1.75	37.7	23
J200S	20	0.44	4.43	9,029	2	3 X 4	1.125	2	5.6
J201S	20	1.625	4.43	9,699	3.65	3.8	2.25	7.2	7
J202S	20	1.75	4.43	9,029	3.75	3.56	2.16	7.7	10
J254S	25	4	5.15	9,699	8.5	3.38	2.25	20.6	17.5
J256S	25	6.3	5.15	9,699	10.75	3.38	2.25	32.2	21.7
J2512S	25	12.25	5.15	9,699	16.75	3.38	2.25	63.2	33
J2514S	25	14.3	5.15	9,699	18.75	3.38	2.25	73.4	40
J300S	30	0.5	6.49	9,242	2.31	3.75 X 4.5	1.38	3.2	8.6
J302S	30	2.4	6.49	9,243	4.625	4	2.5	15.58	14.7
J306S	30	6.25	6.49	9,243	11.13	4	2.5	40.6	23
J500S	50	0.625	9.62	10,395	2.625	4.5	1.75	6	14
J502S	50	2.375	9.62	10,395	4.625	4.88	3.13	22.85	23
J506S	50	6.3	11.04	9,058	11.13	5	3.13	69.55	56
J55.75M	55	0.7	10.6	10,375	1.5	4 X 7.85	0.75	8	7.3
J554S	55	4.25	11.04	9,959	9.1	5	3.13	4	41
J556S	55	6.25	11.04	9,959	11.125	5	3.13	69	51
J5510S	55	10.13	11.04	9,959	15.13	5	3.13	111.8	67
J5513S	55	13.25	11.04	9,959	18.125	5	3.13	146.3	78
J750S	75	0.625	15.9	9,431	3.125		2.13	9.9	23
J751S	75	1	15.9	9,431	2	5.5	4.5	15.9	22
J756S	75	6.125	15.9	9,431	12.375	5.75	3.75	97.4	73.5
J1000S	100	0.625	19.64	10,183	3.38	7 X 6	2.5	12.3	30
J1002S	100	2.25	19.64	10,186	5.5	6.625	3	17.2	52
J1006S	100	6.6	20.62	9,699	13.25	6.25	4.13	137	90
J1500S	150	0.5625	30.68	9,778	4.56	7.5 X 8.5	3	17.2	52
J1502S	150	2	30.68	9,778	6.3	8.06	6.25	61.4	92
J2501S	250	1.25	51.85	9,778	3.13	10	8.13	64.8	70
J2503S	250	3	50.22	9,956	11.875	9.87	5.5	150.6	22
J3556S	355	6	70.88	10,017	13.13	11.7	9.5	425.3	434
J35510S	355	10	70.88	10,017	17.13	11.75	9.5	708.8	565
J4302S	430	2	86.59	9,932	10.38	13	10.5	173.2	440
J4036S	430	6	86.59	9,932	14.38	13	10.5	519.5	609
J5650S	565	0.5	113	9,932	3	14	12	57	92.4
J5651S	565	1.5	113	9,932	4.13	16	12	169.5	174

J5653S	565	3	113.1	9,991	11.75	15	12	353	600
J80012S	800	12	201.06	7,958	27.5	21 X 21	16	2402.4	2,600
J10002S	1000	2	201.06	9,947	6.63	20	16	402	588
J100010S	1000	10	201.06	9,947	36.5	24 X 24	16	2412	5,000
J125020S	1250	20	314.16	7,958	42	30 X 30	20	6283.2	7,200