

Center Hole Jacks - Double Action

Item #	Capacity	Stroke	Area	Pressure	Height	O.D.	Rod Dia.	Oil Ca, cu/in	Weight, lbs	I.D.
J106DC	10	6	2.8	7,143	10.5	3.75	2.5	11	25	1.38
J303DC	30	3	5.89	10,200	7.1	4.75	2.5	17.6	29.8	1.27
J308DC	30	8	7.22	10,000	14	4.5	3.5	57.8	52	1.31
J6010DC	60	10	12.75	9,132	14.6	6.25	4.125	129.1	79	2.13
J1001DC	100	1	21	9,524	7	8.38	5	32	85	3
J1003DC	100	3	21.39	9,350	5.5	8.38	5	64.17	75	3.28
J1006DC	100	6	22.38	8,937	13	7.75	5	68	150	2.13
J1006DC	100	6	20.03	9,986	12.38	7.25	4.38	120.2	95	2.06
J1508DC	150	8	29.85	10,050	13.13	8	5.25	126	162	2.25
J2008DC	200	8	40.45	9,888	16.03	10.75	7.5	202.3	311	4.125
J3008DC	300	8	64.41	9,971	18	13.5	8.5	515.28	425	5.125
J30010DC	300	10	64.41	9,971	20.5	14.5	8.5	644.1	455	4
J4008DC	400	8	88.629	9,987	16.38	16.14	11.02	709.03	715	5.9
J5008DC	500	8	103.67	9,645	20.5	16.88	10.5	829.36	988	5.5
Lightweight Jacks										
J603DCA	60	3	12.75	9,174	7.48	6.25	4.125	38.25	40	2.13
J606DCA	60	6	12.75	9,174	10.48	6.25	4.125	76.5	57	2.13
J1006DCA	100	6	20.04	9,779	17	7.25	4.62	120.2	78	2.13
J1258DCA	125	8	24.76	9,779	13.5	8.37	5.5	198.1	117	3.13
J1506DCA	150	6	30.24	9,921	10.88	8.5	7.25	90	94	3.13
J1508DCA	150	8	30.01	9,971	14	9.37	6.25	240.1	126	3.5
J1758DCA	175	8	37.55	9,971	14.25	9.87	6.75	301	167	3.75
J2008DCA	200	8	42.01	9,971	14.6	10.75	7.5	336.1	198	4.1